



**LUMINAIRE REQUIREMENTS:**

1. CONSTRUCTION: LOW PROFILE SOLID, SEALED SEAMLESS ALUMINUM FRAME FOR STRENGTH 1x4, 2x2, 2x4 WITH A DEPTH OF ONLY 1.26"
2. DRIVER: EXTENDED LIFE HIGH EFFICIENCY WITH L70 AT 60,000 HOURS WITH 0-10VOLT DIMMING STANDARD.
3. LUMENS: 1x4 AND 2x2 SWITCHABLE BETWEEN 2400/3300/4400, 2x4 SWITCHABLE BETWEEN 4000/5000/6000.
4. ELECTRICAL: MVOLT: 3500K, 4000K, 5000K; 80 CRI STANDARD.
5. MOUNTING: T-GRID CEILING  $\frac{1}{16}$ " AND  $\frac{9}{16}$ ", SURFACE, RECESSED HARD CEILING AND SUSPENDED . .
6. EMERGENCY OPTIONS: BATTERY BACKUP.
7. LISTINGS: IC RATED, IP5x RATED, DAMP LOCATION.
8. WARRANTY: 5-YEAR LIMITED WARRANTY.

**DETAIL BASED ON LITHONIA LIGHTING "CPANL" SERIES**

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

**LED LUMEN SWITCHABLE PANEL**