



LUMINAIRE REQUIREMENTS:

1. CONSTRUCTION: DIE-CAST ALUMINUM HOUSING WITH FULLY GASKETED DOOR FRAME. HIGH DURABILITY FINISHES STANDARD.
2. DRIVER: LOW AMBIENT OPTIONS DOWN TO -40°C. HIGH-EFFICIENCY OPTIONS GREATER THAN 125+ LPW.
3. OPTICS: TYPE 2, 3, 4 AND FORWARD THROW DISTRIBUTIONS.
4. LUMENS: 12,000-25,000 AVAILABLE.
5. ELECTRICAL: MVOLT. 347, 480V. OPTIONS. 3000K, 3500K, 4000K, 5000K; 70 CRI, 80 CRI OPTIONS. 6KV SURGE PROTECTION STANDARD. L92 AT 100,000 HOURS.
6. CONTROLS: PHOTOCELL, DUAL SWITCHING, MOTION SENSOR AND NIGHTTAIR WIRELESS OPTION.
7. EMERGENCY: BATTERY BACKUP.
8. LISTINGS: IP66 RATED.
9. WARRANTY: 5-YEAR LIMITED WARRANTY.

DETAIL BASED ON LITHONIA LIGHTING "WDGE4" SERIES

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

ARCHITECTURAL LED WALL SCONCE