



LUMINAIRE REQUIREMENTS:

1. FIXTURE CONSTRUCTION - EXTRUDED ALUMINUM HOUSING UP TO 12 FT LONG. SATIN ANODIZED OR WHITE PAINT FINISH STANDARD. CUSTOM FINISH OPTIONAL.
2. LENGTHS - AVAILABLE IN 12 NOMINAL LENGTHS FROM 1 FT TO 12 FT
3. LENSING - EXTRUDED DR ACRYLIC, SNAP-ON FROSTED WIDESPREAD LENS.
4. LUMENS - LOW, MEDIUM AND HIGH LUMENS PER FT PACKAGES RANGING FROM 450LM/FT - 1244LM/FT.
5. ELECTRICAL - INTEGRAL, UNIVERSAL VOLTAGE: 0-10V DIMMING TO 10% STANDARD; 1% DIMMING OPTIONAL..
6. MOUNTING - SURFACE MOUNT WITH MOUNTING HOLES PREDRILLED.
7. RATINGS - ETL/CSA LISTED FOR DAMP LOCATIONS AND MADE IN THE USA.
8. THIS SKETCH IS A NON-PROPRIETARY GRAPHIC REPRESENTATION OF A LUMINAIRE THAT MAY MEET THE SPECIFICATION REQUIREMENTS. IT IS NOT INTENDED TO INDICATE A CERTAIN MANUFACTURER OR PREFERENCE.

DETAIL BASED ON PRIMUS LIGHTING "ALX7 LED" SERIES

LED UNDERCABINET

REVISED:

LIGHTING PLATE: