



LUMINAIRE REQUIREMENTS:

1. CONSTRUCTION: AIR SUPPLY/RETURN FRAME OPTION. DEPTH OF ONLY 2-3/8". HIGH-EFFICIENCY OPTIONS WITH GREATER THAN 130+ LPW.
2. FORM FACTORS: 1x2, 1x4, 20"x4', 2x2, 2x4.
3. OPTICS: CURVED AND SQUARE DIFFUSERS WITH RIBBED OR SMOOTH FROSTED FINISH.
4. LUMENS: 1,000-12,000 AVAILABLE BASED ON SIZE.
5. ELECTRICAL: 120, 277, 347V, MVOLT. 3000K, 3500K, 4000K, 5000K, 80 CRI AND 90 CRI OPTIONS. L80 AT 60,000 HOURS.
6. CONTROLS: NIGHT WIRED AND WIRELESS, OCCUPANCY SENSORS.
7. EMERGENCY: BATTERY BACKUP.
8. MOUNTING: FITS INTO STANDARD $\frac{1}{16}$ " AND NARROW $\frac{9}{16}$ " T-GRID CEILING SYSTEMS. DRYWALL GRID ADAPTER OPTION.
9. LISTINGS: DAMP LOCATION, IC RATED.
10. WARRANTY: 5-YEAR LIMITED WARRANTY.

DETAIL BASED ON LITHONIA LIGHTING "BLT" SERIES

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

LED LOW-PROFILE FLAT PANEL