



**2x4 VERSION**

LUMINAIRE REQUIREMENTS:

1. FORM FACTORS: 1x4, 2x2, 2x4.
2. LUMENS: 1,500 TO 7,200 AVAILABLE.
3. ELECTRICAL: 120-347V, MVOLT. 3000K, 3500K, 4000K, 5000K; 80 CRI AND 90 CRI.
4. MOUNTING: FITS INTO STANDARD  $\frac{15}{16}$ " AND NARROW  $\frac{9}{16}$ " T-GRID CEILING SYSTEMS. DRYWALL GRID ADAPTER OPTION.
5. CONTROLS: STEP-LEVEL DIMMING, XPOINT WIRELESS NETWORK CONTROLS, EMBEDDED NLIGHT AIR WIRELESS CONTROLS, EMERGENCY BACKUP OPTIONS.
6. EMERGENCY: BATTERY BACKUP, SELF-DIAGNOSTIC BATTERY BACKUP, NLIGHT ENABLED BACKUP AND GENERATOR TRANSFER DEVICE.
7. LISTINGS: DAMP LOCATION, IC RATED, IP5X RATED.
8. WARRANTY: 5-YEAR LIMITED WARRANTY.

**DETAIL BASED ON LITHONIA LIGHTING "ENVEX" SERIES**

| TYPE | LUMENS | LAMP TYPE | INPUT WATTS | VOLTAGE | MOUNTING |
|------|--------|-----------|-------------|---------|----------|
|      |        |           |             |         |          |

**LED VOLUMETRIC TROFFER LIGHTING FIXTURE**