



LUMINAIRE REQUIREMENTS:

1. CONSTRUCTION: STANDARD AND NARROW HOUSING OPTIONS. HIGH AMBIENT OPTIONS UP TO 131°F (55°C). HIGH-EFFICIENCY OPTIONS GREATER THAN 180+ LPW.
2. OPTICS: NARROW, GENERAL, WIDE AND FOCUS DISTRIBUTIONS. SNAP-FIT IP5X DUST-RESISTANT DIFFUSE LENS STANDARD. ROTATABLE OPTICS FROM 30 TO 180 DEGREES.
3. LUMENS: 8,000 TO 72,000 AVAILABLE.
4. ELECTRICAL: 120-480V, MVOLT, HVOLT. 3000K, 3500K, 4000K, 5000K; 80 CRI (STANDARD), 90 CRI (OPTION). 6kV SURGE PROTECTION WITH 10kV OPTION. L92 AT 60,000 HOURS.
5. MOUNTING: SUITABLE FOR SUSPENSION BY CHAIN, CABLE, SURFACE WHEN USING COMPATIBLE SURFACE BRACKET, AND HOOK MONOPOINT OR SINGLE (PENDANT).
6. CONTROLS: 0-10V DIMMING, XPOINT WIRELESS NETWORK CONTROLS, EMBEDDED NIGHT AIR WIRELESS CONTROLS, EMERGENCY BACKUP OPTIONS.
7. LISTINGS: DAMP LOCATION.
8. WARRANTY: 5-YEAR LIMITED WARRANTY.

DETAIL BASED ON LITHONIA LIGHTING "IBG" SERIES

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

LED LINEAR HIGHBAY LIGHTING FIXTURE