



LUMINAIRE REQUIREMENTS:

1. CONSTRUCTION: SUITABLE FOR AMBIENT TEMPERATURES FROM -40°F TO 149°F. CORROSION RESISTANT FINISH OPTION. WIRE GUARD OPTION.
2. OPTICS: ONE PIECE PRECISION MOLDED 0.375" THICK BOROSILICATE GLASS THAT IS SILICONE GASKETED. WIDE, NARROW AND MEDIUM DISTRIBUTION OPTIONS.
3. LUMENS: 12,000 TO 60,000 AVAILABLE.
4. ELECTRICAL: 120-480V, MVOLT, HVOLT, 3500K, 4000K, 5000K; 70 CRI, 80 CRI, 90 CRI OPTIONS. 6KV SURGE PROTECTION WITH 10KV OPTION. L70 AT 100,000 HOURS.
5. MOUNTING: ¾" NPS THREADED HUB STANDARD SUITABLE FOR PENDANT, HOOK OR LOOP.
6. CONTROLS: 0-10V DIMMING, MOTION SENSOR, XPOINT WIRELESS NETWORK CONTROLS, EMBEDDED NLIGHT AIR WIRELESS CONTROLS.
7. EMERGENCY: BATTERY BACKUP WITH SELF DIAGNOSTIC OPTIONS.
8. LISTINGS: WET LOCATION, IP65 RATED.
9. WARRANTY: 5-YEAR LIMITED WARRANTY.

DETAIL BASED ON LITHONIA LIGHTING "JHBL" SERIES

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

LED ROUND HIGHBAY LIGHTING FIXTURE