



LUMINAIRE REQUIREMENTS:

1. CONSTRUCTION: HIGH AMBIENT OPTIONS UP TO 131°F (55°C). HIGH-EFFICIENCY OPTIONS GREATER THAN 150+ LPW. FULL VISOR OPTION. BIRD SPIKES OPTION.
2. OPTICS: NARROW, WIDE AND MEDIUM FLOOD AND SPOT FOCUS DISTRIBUTIONS.
3. LUMENS: 11,000 TO 31,000 AVAILABLE.
4. ELECTRICAL: 120-480V, MVOLT, HVOLT, XVOLT. 3000K, 4000K, 5000K. 10kV SURGE PROTECTION WITH 20kV OPTION. L92 AT 100,000 HOURS.
5. MOUNTING: ADJUSTABLE SLIPFITTER, YOKE, AND ADJUSTABLE TILT ARM FOR ROUND, SQUARE OR WALL BRACKET.
6. CONTROLS: 0-10V DIMMING, PHOTOCCELL, NLIGHT AIR WIRELESS CONTROLS.
7. LISTINGS: WET LOCATION.
8. WARRANTY: 5-YEAR LIMITED WARRANTY.

DETAIL BASED ON LITHONIA LIGHTING "RSXF2" SERIES

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

LED FLOODLIGHT FIXTURE