



LUMINAIRE REQUIREMENTS:

1. CONSTRUCTION: DIE-CAST ALUMINUM HOUSING WITH FULLY GASKETED DOOR FRAME. HIGH DURABILITY FINISHES STANDARD.
2. DRIVER: LOW AMBIENT OPTIONS DOWN TO -40°C. HIGH-EFFICIENCY OPTIONS GREATER THAN 110+ LPW.
3. OPTICS: VISUAL COMFORT FORWARD THROW AND WIDE DISTRIBUTIONS.
4. LUMENS: 1,200-2,000 AVAILABLE.
5. ELECTRICAL: MVOLT, 347 OPTIONS, 2700K, 3000K, 3500K, 4000K, 5000K; 80 CRI (STANDARD), 90 CRI (OPTION), 6KV SURGE PROTECTION STANDARD, L91 AT 100,000 HOURS.
6. CONTROLS: PHOTOCELL AND DUAL SWITCHING OPTION.
7. EMERGENCY: BATTERY BACKUP.
8. LISTINGS: IP66 RATED.
9. WARRANTY: 5-YEAR LIMITED WARRANTY.

DETAIL BASED ON LITHONIA LIGHTING "WEDGE1" SERIES

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

ARCHITECTURAL LED WALL SCONCE