



LUMINAIRE REQUIREMENTS:

1. CONSTRUCTION: DIE-CAST ALUMINUM HOUSING WITH SILICONE GASKETS, WIRE GUARD OPTION.
2. OPTICS: NARROW, MEDIUM AND WIDE DISTRIBUTIONS, FROSTED AND CLEAR GLASS AND FROSTED, CLEAR, AND TEXTURED ACRYLIC LENS OPTIONS.
3. LUMENS: 12,000-30,000 AVAILABLE IN 24", 24,000-42,000 AVAILABLE IN 48".
4. ELECTRICAL: 120-480V, MVOLT, HVOLT, 3000K, 3500K, 4000K, 5000K; 70, 80 AND 90 CRI OPTIONS, 10KV SURGE PROTECTION, L91 AT 60,000 HOURS, L86 AT 100,000 HOURS.
5. MOUNTING: SUITABLE FOR SUSPENSION BY PENDANT, (SINGLE MONOPOINT), CHAIN OR CABLE, SURFACE MOUNT WITH COMPATIBLE SURFACE OR YOKE MOUNT BRACKET.
6. CONTROLS: MOTION SENSOR, NIGHT WIRELESS CONTROLS.
7. EMERGENCY: BATTERY BACKUP.
8. LISTINGS: WET LOCATION.
9. WARRANTY: 5-YEAR LIMITED WARRANTY.

DETAIL BASED ON LITHONIA LIGHTING "XIB" SERIES

TYPE	LUMENS	LAMP TYPE	INPUT WATTS	VOLTAGE	MOUNTING

LED LINEAR HIGHBAY LIGHTING FIXTURE